

DETAILS


Aratri Disc Ploughs designed to work in all types of soil for functions such as soil breaking, soil raising, soil turning and soil mixing. Beside, they are used to open the new fields and to process the stony areas, can be used at rocky and rooted lands. It is specially useful in hard and dry trashy land conditions and in soils where scouring is a major problem. Aratri Disc Ploughs are ranging from 2,3,4,5 and 6 furrows. While processing, it prevents the occurrence of the big holes and mudding the upper part of furrows. There is no possibility to stop up because of grass, helves and farm fertilizer. Its’ special design allows to easier ploughing. By these features, the damage that may occur in disc ploughs and tractor can be prevented.The exposure time of plough chassis and discs are rather long. Particularly the discs are boron steel from Turkey, 52-55 Rhe hardness, Ø660 or Ø710 mm and are adjustable to get the maximum performance from the tractor.

Aratri DISC PLOUGH

TECHNICAL FEATURES	UNIT	MODEL			
		ARATRI 266	ARATRI 366	ARATRI 466	ARATRI 566
Number of Discs	pcs	2	3	4	5
Total Length	mm	1155	2130	2520	2910
Total Width	mm	1115	1265	1420	1520
Total Height	mm	1235	1235	1235	1235
Working Depth	cm	25	25	25	25
Working Width	cm	66	99	132	165
Space of Discs	cm	53	53	53	53
Dia. of disc	mm	710	710	710	710
Required Power	hp	45-50	65-70	80-90	90-105
Total Weight	kg	310	400	470	540



OPTIONAL FEATURES



28"/710 mm Disc