DETAILS

Tractor trailed mist blowers Arrosto for professional use were created with an aim to deliver accurate and efficient spray application and by taking into account the need to reduce adverse environmental impacts. They were designed for fruit producers that require sophisticated machines with particular emphasis on quality and outstanding spraying results. Polyethylene Tanks with a capacity of 1000, 1200, 1600, 2000 and 3000 lt, have rinsing and hand-rinsing tank in Arrosto Plus Model.

The mist blower features a chassis made from high-quality steel to ensure a long service life. The chassis is designed to ensure efficient mixing of spraying agent, complete drainage of the tank and easy cleaning. The tow-bar consists of a movable and rigid towing eye, enabling the mist blower to follow the tractor wheel tracks. In addition to the pumps we have produced, we also offer optional Italian pumps to our customers, like Comet or Bertollini. Arrosto Turbo Mistblowers are operated by power take-off from tractor conveys pressuring chemical liquid to nozzles on fan. Fan is also operated with power take off and it sends pressured air out. Pressured chemical liquid is sprayed by adjustable nozzles around the fan by air circulation and any kind of tree can be disinfected. Fans are operated by two speed transmissions. Atomization is possible on right or left sides by remote control. Modern sand blasting and powder coating methods provides an effective protection of the frame of our all kind of sprayers.

TURBO MISTBLOWER

| TECHNICAL FEATURES | UNIT | MODEL | | | | |
|--------------------|-----------|--------------------|--------------------|--------------------|--------------------|--------------------|
| | | ARROSTO+ 1000 | ARROSTO+ 1200 | ARROSTO+ 1600 | ARROSTO+ 2000 | ARROSTO+ 3000 |
| Capacity | lt | 1000 | 1200 | 1600 | 2000 | 3000 |
| Pump | type | 105 or 145 |
| Flow Rate | l/min | 105 or 145 |
| Pressure | bar | 50 | 50 | 50 | 50 | 50 |
| Rotation | rev / min | 540 | 540 | 540 | 540 | 540 |
| Fan Diameter | cm | 75 or 85 |
| Fan Flow Rate | m³/h | 66000 | 66000 | 66000 | 66000 | 66000 |
| Power Transfer | | Dual-Speed Gearbox |
| Nozzle | pcs. | 10 or 14 |
| Width | mm | 1300 | 1450 | 1600 | 1700 | 1600 |
| Length | mm | 3750 | 3750 | 3800 | 3900 | 4700 |
| Height | mm | 1330 | 1330 | 1380 | 1450 | 1550 |
| Weight | kg | 540 | 550 | 620 | 650 | 800 |



FERTILIZING AND PLANT PROTECTION



OPTIONAL FEATURES





Cover Inside Mixer





C Type Drawbar





Angular Fan



Traffic Set







Chrome Nickel Fan Hot Dip Galvanized