DETAILS

Eva No-Till Mechanical Direct Seeder is trailed sowing machine which can plant seeds of all kinds of grains and all kinds of fertilizer precisely and properly on cultivated, semi-cultivated or uncultivated soils. It is manufactured as 14,18,21 and 29 rows. Thanks to its functionality to work under heavy soil conditions, it can sow seeds in all sizes precisely. The machine which is adjusted easily and has a strong structure, sows properly under all kinds of soil and land conditions. Thanks to its towed-structure, it does not need much power from your tractor.

Eva operates in the field by opening the seedbed through a set of notched cutter disc and plain disc, with these special design seeding rows, the seed and fertilizer is placed at the correct depth. Afterward, seed bed is compacted through the pressure wheels which is rims are casting. The mechanism for depth control and precision has been designed hydraulically like our Lina Seeders. The enlarged disc tine has internal scraper and pressure wheels have external scrapers that keeps the them clean. This permits the drill to work even in the wettest conditions.

Both seed and fertilizer rate adjustment are done by changing the axle speed steplessly with the gearbox. Drive is supplied by the land wheel. Additionally, we are offering End tow (transport system on road) to easy carrying of the machine.

Eva

NO-TILL MECHANICAL DIRECT SEEDER

TECHNICAL FEATURES	UNIT —	MODEL			
		EVA 14	EVA 18	EVA 21	EVA 29
Number of Rows	qty	14	18	21	29
Working Width	mm	2000	2500	3000	4000
Row Distance	cm	14	14	14	14
Seed Hopper Capacity	lt	600	730	880	1150
Length	mm	3900	3900	3900	3900
Height	mm	2000	2000	2000	2000
Width	mm	3300	3800	4200	5200
Tyre Size	inch	10.75/15.3	10.75/15.3	10.75/15.3	10.75/15.3
Weight	kg	2200	2600	3100	4100
Required Power	hp	110+	120+	130+	170+







OPTIONAL FEATURES







Hydraulic Tramline Electronic Tramline Digital Decarmeter





Traffic S

www. agroleac