SOWING AND PLANTING

Liva Pneumatic Planter Slide model has designed to response hydraulic controlled planter units in shortest time. Machine is useful and time saver during operation of row spacing and over row sowing of all kinds of seeds (beet, corn, sunflower, cotton, onion, sweet melon, watermelon, groundnut etc.) at desired quantity sensitively. Liva Slide model pneumatic planter has been added to our product range as the newest generation seeder produced by our company. Liva Slide Models are ranging at 4 and 6 Rows, with and without fertilizing options. Upon request, fertilizer tank and fertilizing kit installed on the machine as three types, inox, plastic and steel materials. Fertilizer tanks are in "V" shape, have sieves and fertilizer discharge levers for easy cleaning after sowing. Pneumatic seeder provides a sensitive sowing since it transfers the motion activity generated by the wheels, to the seeder units with the help of shaft allowing easy adjustment of over row distance. Thanks to these specifications, it allows sowing on all kinds of soil conditions and dropping fertilizer and seed into the equal depth. We are offering all Liva Pneumatic Planters with hydraulic side markers as standard feature of the machines.

## **SLIDE UNITS** PNEUMATIC PLANTER

TECHNICAL FEATURES	UNIT	MODEL			
		LIVA 4S	LIVA 4SF	LIVA 6S	LIVA 6SF
Number of Rows	qty	4	4	6	6
Width	mm	3300	3300	4000	4000
Length	mm	2300	2300	2300	2300
Height	mm	1500	1600	1500	1600
Seed Hopper Volume	lt	4x35	4x35	6x35	6x35
Fertilizer Hopper Volume	lt	-	2x200	-	2x200
Disc Hole Diameter	mm	1*6	1*6	1*6	1*6
Disc Hole Number	pcs	Variable	Variable	Variable	Variable
Distance Between Rows	cm	50-95	50-95	45-50-55-60-65-70	45-50-55-60-65-70
Intrarow Distance	cm	1-177	1-177	1-177	1-177
Working Speed	km/h	6*8	6*8	6*8	6*8
Required Power	hp	70+	80+	90+	100+
Weight	kg	1100	1250	1250	1450





## **OPTIONAL FEATURES**






Hopper



Straw Cleaner













Controller