

DETAILS

Insta Fertilizer Spreader are produced for professional purposes and are mounted to the tractor through three-point linkage system. Main tank is 900 lt and the capacity of the machines can be increased with the sideboards up to 3000 lt. Dosage of the fertilizer are hydraulically controlled in Insta Spreaders. Thanks to this feature, fertilizers are easily and quickly spreaded at the beginning of the border through control from the tractor cabin thus unnecessary fertilizer consumption is prevented. Fertilizer tank is divided in two pieces with opposite V shaped separative that is under the tank and the mixer shaft in the fertilizer tank is located in a horizontal position and rotates with low rev. These inox mixer shafts never powder the fertilizer during operation. By this way, distribution of the fertilizer into the field is more homogeneous and fluidal. Despite the erosion caused by the chemical fertilizers you have used, all parts that come into contact with the fertilizer are made of inox material.

Insta

FERTILIZER SPREADER



TECHNICAL FEATURES	UNIT	MODEL				
		INSTA 900	INSTA 1200	INSTA 1500	INSTA 1800	INSTA 2000
Capacity	kg	900	1200	1500	1800	2000
Standard Working Width	mt	16-24	16-24	16-24	16-24	16-24
Optional Working Width	mt	10-16 / 24-36	10-16 / 24-36	10-16 / 24-36	10-16 / 24-36	10-16 / 24-36
Disc Set	mtrl	Inox	Inox	Inox	Inox	Inox
Dispensers on Disc	pcs	2	2	2	2	2
Rotation of Discs	rev / min	720	720	720	720	720
Working Speed	km/h	15-20	15-20	15-20	15-20	15-20
Dosage Adjustment	ctrl	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Height	mm	1380	1430	1680	1810	1900
Width	mm	2280	2350	2350	2350	2350
Length	mm	1500	1500	1500	1500	1500
Weight	kg	385	400	415	435	460
Required Power	hp	50+	55+	60+	65+	70+

OPTIONAL FEATURES



24/36 mt Disc



Inox Limiter



Inox Protector